

## EDGE Stick Machine Preventive Maintenance

CUSTOMER INFORMATION			
CUSTOMER		EMAIL	
ADDRESS			PHONE
CITY	ST	ZIP	CONTACT

MACHINE INFORMATION
SERIAL #
WORK ORDER #
CHASSIS HOUR METER (optional)

NOTE: Isolators need to be replaced on Floor Machines at 250 hours or annually

DECK CONDITION			
EDGE Pad Grip Face	Good	Worn	Needs Replacement
Spacer Pad	Good	Worn	Needs Replacement

CHECK OPERATION AND CONDITION OF:	IN SPEC	REPAIR	PROBLEM
Trigger Key Switch (optional)			
Solution Lever			
Deck Motor			
Inspect AC Cord (Replace if damaged)			
Inspect edge of Aluminum Deck (Report if damaged)			
Vacuum Motor Performance (optional)			

MEASURE GAP AT 4 CORNERS	FRONT RIGHT	FRONT LEFT	REAR RIGHT	REAR LEFT
Between Aluminum and Steel Decks				

CLEAN AND/OR LUBRICATE	IN SPEC	REPAIR	PROBLEM
Solution Tank Condition			

VISUALLY INSPECT	IN SPEC	REPAIR	PROBLEM
Vacuum Hoses (optional)			
Solution Hoses (optional)			
Machine Wheels			
Dust Skirts (optional)			

COMMENTS

Servicing Distributor \_\_\_\_\_

Technician's Name \_\_\_\_\_ Date \_\_\_\_\_ Signature \_\_\_\_\_

Customer's Name: \_\_\_\_\_ Date \_\_\_\_\_ Signature \_\_\_\_\_