




GTX Scrubber  
Specifications



**Disc**

**Cylindrical**

**BODY CONSTRUCTION / DIMENSIONS**

Tank Material:	Poly (3/8" (.95 cm) thick)	Poly (3/8" (.95 cm) thick)
Chassis Construction:	3/16" Steel (.3175 cm)	3/16" Steel (.3175 cm)
Rear Wheels (diameter x width):	(2) 12" x 5" (30 x 13 cm)	(2) 12" x 5" (30 x 13 cm)
Size (L x W x H):	54" x 26" x 55" (137/63/140 cm)	54" x 26" x 55" (137/63/140 cm)
Weight:	780 lbs. (354 kg)	780 lbs. (354 kg)
Weight (w / 245 ah batteries):	1,222 lbs. (554 kg)	1,222 lbs. (554 kg)

**BRUSH SYSTEM:**

Brush Size:	26D: (2) 13" [(2) 33 cm] 30D: (2) 15" [(2) 33.5 cm] 34D: (2) 17" [(2) 43 cm]	24C: (2) 22" [(2) 55 cm] 27C: (2) 25" [(2) 63.5 cm] 30C: (2) 28" [(2) 71 cm] 34C: (2) 32" [(2) 81 cm]
Standard Brush Motor:	(2) 0.75 hp (559 watts) / 300 rpm	(2) 0.75 hp (559 watts) / 750 rpm
Optional Brush Motor:	(2) 1.0 hp (746 watts) / 350 rpm	NA
Brush Speed:	300 rpm	750 rpm
EDGE Pad Size:	28-EDGE (1) 28" x 14" 32-EDGE (1) 32" x 14"	28-EDGE (1) 28" x 14" 32-EDGE (1) 32" x 14"
EDGE Pad Motor	(1) 1.0 hp (780 watts) / 2000 or 2500 rpm	(1) 1.0 hp (780 watts) / 2000 or 2500 rpm
Brush Down Pressure:	0-250 lbs. (0 - 113 kg)	0-250 lbs. (0 - 113 kg)
Actuator Rating	500 lbs. (227 kg)	500 lbs. (227 kg)

**BATTERY SYSTEM:**

System Voltage:	36 volts	36 volts
Standard Battery Rating:	245 AH	245 AH
Optional Battery Rating:	325 AH	325 AH
Battery Run Time:	Up to 7 hours	Up to 7 hours
Charger (110-v / 60 Hz / 24-volt):	36-v / 25 amp	36-v / 25 amp

**SOLUTION SYSTEM:**

Solution Tank Capacity:	35 gal. (132 liters)	35 gal. (132 liters)
Solution Flow Rate:	0-1.5 gpm (0-6 lpm)	0-1.5 gpm (0-6 lpm)
Solution Filter:	Stainless Inline	Stainless Inline

**RECOVERY SYSTEM:**

Recovery Tank Capacity:	35 gal. (132 liters)	35 gal. (132 liters)
Vacuum Power:	1.0 hp (746 watts)	1.0 hp (746 watts)
Drain Hose:	2.0" (5 cm) Diameter	2.0" (5 cm) Diameter
Vacuum (lift / airflow):	68" / 70 cfm (173 cm / 21 cmm)	68" / 70 cfm (173 cm / 21 cmm)
Demisting Chamber:	3 gal. (11 liters)	3 gal. (11 liters)

**DRIVE SYSTEM:**

Power:	1.0 hp (746 watts), sealed	1.0 hp (746 watts), sealed
Speed Control:	Variable 0-320 ft. (0-97 m)	Variable 0-320 ft. (0-97 m)

**GENERAL:**

Minimum Aisle U-Turn	56" (142 cm)	56" (142 cm)
Sound Level:	68 dBA	68 dBA
Cleaning Width & Rate/Hour:	26D: 28,600 sq. ft./hr. (8,717 m <sup>2</sup> /hr.) 30D: 33,000 sq. ft./hr. (10,058 m <sup>2</sup> /hr.) 34D: 37,400 sq. ft./hr. (11,399 m <sup>2</sup> /hr.)	24C: 26,400 sq. ft./hr. (8,047 m <sup>2</sup> /hr.) 27C: 29,700 sq. ft./hr. (9,052 m <sup>2</sup> /hr.) 30C: 33,000 sq. ft./hr. (10,058 m <sup>2</sup> /hr.) 34C: 37,400 sq. ft./hr. (11,399 m <sup>2</sup> /hr.)

**RPS CORPORATION**

P.O. Box 368  
Racine, WI 53401  
Phone: (800)634-4060  
Fax: (866)901-3335

© RPS Corporation 2010.  
All Rights Reserved.

Since our policy is one of constant improvement,  
all specifications are subject to change without notice.

**AUTHORIZED DISTRIBUTOR**