


MINIMAG

Walk Behind Scrubber Specifications



MINI 17", 20", 23"

MINIMAG 17", 20", 23", 24", 26", 28"

BODY CONSTRUCTION / DIMENSIONS:

Tank Material:	Poly (3/8" thick) (.9525 cm)	Poly (3/8" thick) (.9525 cm)
Chassis Construction:	3/16" Coated Steel (2 cm)	3/16" Coated Steel (2 cm)
Front Wheels:	(2) 9" x 2" (23 cm x 5 cm)	(2) 9" x 3" (23 cm x 8 cm)
Rear Casters:	(2) 4" x 2" (10 cm x 5 cm)	(2) 4" x 2" (10 cm x 5 cm)
Size (L x W x H):	45" x 18" x 40" (114 cm x 46 cm x 102 cm)	45" x 18" x 40" (114 cm x 46 cm x 102 cm)
Weight (w/o batteries)	242 lbs (110 kg)	255 lbs (116 kg)
Weight (w/batteries)	374 lbs (170 kg)	387 lbs (176 kg)

BRUSH SYSTEM:

Disk Brush/Pad Size:	17-D: (1) 17" (43 cm) 20-D: (1) 20" (51 cm) 23-D: (1) 23" (58 cm)	17-D: (1) 17" (43 cm) 20-D: (1) 20" (51 cm) 23-D: (1) 23" (58 cm) 26-D: (2) 13" [(2)33 cm] 28-D: (2) 14" [(2)35.5 cm]
Disk Brush Motor	(1) .75 hp (559 watts)/ 200 rpm	(1 or 2) .75 hp (559 watts)/ 270 rpm
Cylindrical Brush Size:	NA	24-C (2) 22" x 5.5"
Cylindrical Brush Motors	NA	(2) .75 hp (559 watts)/ 750 rpm
Edge Pad Size:	NA	20-Edge (1) 20" x 14" 28-Edge (1) 28" x 14"
Edge Pad Motor	NA	(1) 1.0 hp (780 watts)/ 2000 or 2500 rpm
Brush Down Pressure:	0-125 lbs (0-57 kg)	0 - 150 lbs (0-68 kg)

BATTERY SYSTEM:

System Voltage	24 volts	24 volts
Standard Battery Rating:	115 ah	155 ah
Optional Battery Rating:	up to 225 ah	225 ah
Battery Run Time:	Up to 3.5 hours	Up to 4 hours
Charger (110-v / 60 Hz / 24-volt):	Dual Mode Console	Dual Mode Console

SOLUTION SYSTEM:

Solution Tank Cap.:	17 gallons (64 liters)	17 gallons (64 liters)
Solution Flow Rate:	0 - 1.0 gpm (0 - 4 lpm)	0 - 1.0 gpm (0 - 4 lpm)
Solution Filter:	Stainless / Inline	Stainless / Inline

RECOVERY SYSTEM:

Recovery Tank Cap.:	17 gallons (64 liters)	17 gallons (64 liters)
Vac. Power:	0.75 hp (559 watts)	0.75 hp (559 watts)
Drain Hose:	1.5" (4 cm) diameter	1.5" (4 cm) diameter
Vacuum Specs (lift / airflow):	70" / 70 cfm (178 cm / 21 cmm)	70" / 70 cfm (178 cm / 21 cmm)
Demisting Chamber:	1.25 gallons (5 liters)	1.25 gallons (5 liters)
Drain Saver:	30 cubic inches (70 cubic cm)	30 cubic inches (70 cubic cm)

GENERAL:

Cleaning Width:	17-BD: 17" (43 cm) 20-BD: 20" (51 cm) 23-BD: 23" (58 cm)	17-D: 17" (43 cm) 20-D: 20" (51 cm) 23-D: 23" (58 cm) 26-D: 26" (66 cm) 28-D: 28" (71 cm) 24-C: 24" (61 cm) 20-Edge: 20" (51 cm) 28-Edge: 28" (71 cm)
Cleaning Rate/Hour (Sq.Ft./Hr):	Up to 22,124 (6,743 m)	Up to 25,543 (7,786 m)
Sound Level:	67 dBA	67 dBA

DRIVE SYSTEM:

Standard Drive:	Brush Drive	0.75 hp (559 watts), all gear / sealed
Forward Speed:	0-230 ft/min (4 mph) (6 kph)	0-230 ft/min (4 mph) (6 kph)
Reverse Speed:	0-130 ft/min (2 mph) (3 kph)	0-130 ft/min (2 mph) (3 kph)

RPS CORPORATION

P.O. Box 368
Racine, WI 53401
Phone: (800)634-4060
Fax: (866)901-3335

© RPS Corporation 2010.
All Rights Reserved.

Since our policy is one of constant improvement,
all specifications are subject to change without notice.

AUTHORIZED DISTRIBUTOR